

toll free: 800-929-9473

CATEGORY 3 PREMISE CABLE UTP - UNSHIELDED TWISTED PAIRS TYPE CMP, PLENUM RATED, SIZES #24 & 22AWG

CONSTRUCTION:

CONDUCTOR SOLID ANNEALED BARE COPPER.

INSULATION PLENUM RATED PVC COPOLYMER, COLOR CODED PER TELEPHONE COLOR CODE.

CORE ASSEMBLY INSULATED CONDUCTORS TWISTED INTO PAIRS OR VARYING TWIST LENGTHS TO MINIMIZE CROSSTALK AND CABLED

TOGETHER.

JACKET PLENUM RATED PVC COPOLYMER.

Charlotte	0:	Number	Overall	Approx.
Wire Part#	Size AWG	of Pairs	Diameter (in.)	Net Wt. (Lbs/Mft)
			<u> </u>	
CW09626	24	2	.14"	11
CW09627	24	3	.15"	15
CW09628	24	4	.17"	19
CW09629	24	6	.20"	27
CW09630	24	8	.22"	36
CW09631	24	12	.26"	51
CW09632	24	25	.36"	102
CW09633	24	50	.51"	199
CW09634	24	75	.59"	288
CW09635	24	100	.68"	382
CW09636	24	200	1.04"	740
CW09637	24	300	1.28"	1090
CW09638	22	2	.16"	16
CW09639	22	3	.17"	21
CW09640	22	4	.19"	27
CW09641	22	6	.22"	40
CW09642	22	12	.30"	70
CW09643	22	25	.41"	148

APPLICATION:

Suitable as plenum rated cable in Local Area Networks up to 16MHz. Used for voice transmission, data transmission, and other indoor phone cable installations.

STANDARDS:

NEC Article 800: Type CMP.