

MULTICONDUCTOR PLENUM CABLE NONSHIELDED - SIZES 22 & 20 AWG NEC ARTICLES 725/800, TYPE CL2P, CL3P, OR CMP

CONSTRUCTION:

CONDUCTOR SOLID OR STRANDED BARE COPPER.

INSULATION PLENUM RATED PVC COPOLYMER INDIVIDUALLY COLOR CODED PER CHART BELOW.

JACKET PLENUM RATED PVC COPOLYMER COLORED WHITE/NATURAL.

Charlotte Wire Part#	Size AWG	Number of Conductors	Number of Strands	Insulation Thickness (in.)	Jacket Thickness (in.)	Overall Diameter (in.)	Approx. Net Wt. (Lbs/Mft.)
CW09351	22	2	Solid	.008"	.015"	.12"	9
CW09352	22	3	Solid	.008"	.015"	.12"	11
CW09353	22	4	Solid	.008"	.015"	.13"	13
CW09354	22	12	Solid	.008"	.015"	.20"	40
CW09355	22	2	7	.008"	.015"	.13"	10
CW09356	22	3	7	.008"	.015"	.14"	12
CW09357	22	4	7	.008"	.015"	.15"	15
CW09358	22	5	7	.008"	.015"	.16"	19
CW09359	22	6	7	.008"	.015"	.17"	22
CW09360	22	8	7	.008"	.015"	.18"	27
CW09361	22	10	7	.008"	.015"	.21"	33
CW09362	22	12	7	.008"	.015"	.22"	40
CW09367	22	15	7	.008"	.015"	.26"	52
CW09363	20	2	7	.008"	.015"	.14"	12
CW09364	20	3	7	.008"	.015"	.15"	17
CW09365	20	4	7	.008"	.015"	.16"	21
CW09366	20	5	7	.008"	.015"	.18"	25

APPLICATION:

Suitable for use in ducts, plenums, and other space used for environmental air and shall also be listed as having adequate fire resistant and low smoke producing characteristics. Used in sound/audio systems, intercom/P.A. systems, security systems, power limited controls, and remote control signaling.

STANDARDS:

NEC Article 725 (Type CL2P and CL3P).
NEC Article 800 (Type CMP).

Color Code Chart:

Conductor#	Color	Conductor#	Color
1st	Black	7th	Orange
2nd	Red	8th	Yellow
3rd	White	9th	Purple
4th	Green	10th	Gray
5th	Brown	11th	Pink
6th	Blue	12th	Tan