



“Taking Care of Business”

toll free: 800-929-9473

**150DEGREES C XLP LEAD WIRE
FLEXIBLE STRANDED TINNED COPPER
UL AWM STYLE 3321 , CSA LISTED**

CONSTRUCTION:

CONDUCTOR FLEXIBLE STRANDED TINNED COPPER.

INSULATION CROSSLINKED POLYETHYLENE (XLP).

Charlotte Wire Part#	Size AWG	Number of Strands	Insulation Thickness (in.)	Overall Diameter (in.)	Approx. Net Weight (Lbs/Mft.)
CW04270	22	7	.030"	.10"	5
CW04271	20	10	.030"	.11"	7
CW04272	18	16	.030"	.12"	11
CW04273	16	26	.030"	.13"	14
CW04274	14	41	.030"	.14"	20
CW04275	12	65	.030"	.16"	30
CW04276	10	105	.030"	.19"	42
CW04277	8	133	.045"	.26"	68
CW04278	6	133	.045"	.31"	105

APPLICATION:

Suitable for internal appliance wiring and machine tool wiring. May be used in transformers, switchboard panels, controls, electronic circuits, motors, power hook-up applications, and uninterrupted power supply systems.

STANDARDS:

UL AWM Style 3321: 600Volts 150Degrees C.
CSA CL1503.